

LINE INTERACTIVE UPS

UPS NT-V625-DA



Main features:

- CPU controlled
- Auto re-starts when AC recovers
- Silence setup
- Automatic charging (offline charging)
- Battery low voltage protection
- Overload & short circuit protection
- Wide input voltage range

TECHNICAL SPECIFICATION

| MODEL | NT-V625-DA | |
|-------------|-------------------------------------------------------------------|---------------------------------------------|
| Capacity | 600VA/360W | |
| Input | Voltage | 110/120Vac or 220/230/240Vac |
| | Voltage range | 85-150Vac / 165-265Vac |
| | Frequency range | 46-54Hz |
| Output | Voltage | 110/120 VAC or 220/230/240 VAC \pm 10% |
| | Frequency range | 60 \pm 1Hz or 50 \pm 1Hz (Battery mode) |
| | Transfer time | Typical 2-6ms. 10ms max |
| | Wave form | PWM (Battery mode) |
| Battery | Battery model & Quantity | 12V/7AH X 1pc |
| | Charge period | 4-6 hours recover to 90% capacity |
| | Backup time | Full load 8 minutes, halfload 16 minutes |
| Protection | Full protection: Low voltage, overload & short circuit protection | |
| Physical | Unit dimension(mm) | 300*95*140 |
| | Net weight(kg) | 4.3 |
| Environment | Environment of performance | Temperature 0°C-40°C, Humidity 20%-90% |
| | Noise level | \leq 40dB(1m) |
| Management | LCD or LED, RJ45/11 & USB (optional) | |